

RCCN 日成DIN铜管端子 DIN Copper Tube Terminals



DIN46235



型号 Item No.	尺寸 DIMENSION					
	E	D ϕ	d ϕ	W	B	L
DIN6-5	5.3	5.5	3.8	8.5	10.0	30.5
DIN6-6	6.4	5.5	3.8	8.5	10.0	31.5
DIN6-8	8.4	5.5	3.8	13.0	10.0	34.0
DIN10-5	5.3	6.0	4.5	9.0	10.0	34.0
DIN10-6	6.4	6.0	4.5	9.0	10.0	34.5
DIN10-8	8.4	6.0	4.5	13.0	10.0	37.0
DIN10-10	10.5	6.0	4.5	15.0	10.0	39.0
DIN16-6	6.4	8.5	5.5	13.0	20.0	43.5
DIN16-8	8.4	8.5	5.5	13.0	20.0	46.0
DIN16-10	10.5	8.5	5.5	17.0	20.0	48.0
DIN16-12	13.0	8.5	5.5	18.0	20.0	49.0
DIN25-6	6.4	10.0	7.0	14.0	20.0	45.5
DIN25-8	8.4	10.0	7.0	16.0	20.0	48.0
DIN25-10	10.5	10.0	7.0	17.0	20.0	50.0
DIN25-12	13.0	10.0	7.0	19.0	20.0	51.0
DIN35-6	6.4	12.5	8.2	17.0	20.0	49.5
DIN35-8	8.4	12.5	8.2	17.0	20.0	52.0
DIN35-10	10.5	12.5	8.2	19.0	20.0	54.0
DIN35-12	13.0	12.5	8.2	21.0	20.0	55.0
DIN35-14	15.0	12.5	8.2	21.0	20.0	56.5
DIN50-8	8.4	14.5	10.0	20.0	28.0	62.0
DIN50-10	10.5	14.5	10.0	22.0	28.0	64.0
DIN50-12	13.0	14.5	10.0	24.0	28.0	65.0
DIN50-14	15.0	14.5	10.0	24.0	28.0	66.5
DIN50-16	17.0	14.5	10.0	28.0	28.0	68.0

型号 Item No.	尺寸 DIMENSION					
	E	D ϕ	d ϕ	W	B	L
DIN70-8	8.4	16.5	11.5	24.0	28.0	65.0
DIN70-10	10.5	16.5	11.5	24.0	28.0	67.0
DIN70-12	13.0	16.5	11.5	24.0	28.0	68.0
DIN70-14	15.0	16.5	11.5	24.0	28.0	69.5
DIN70-16	17.0	16.5	11.5	30.0	28.0	71.0
DIN95-8	8.4	19.0	13.5	28.0	35.0	77.0
DIN95-10	10.5	19.0	13.5	28.0	35.0	77.0
DIN95-12	13.0	19.0	13.5	28.0	35.0	78.0
DIN95-14	15.0	19.0	13.5	28.0	35.0	79.5
DIN95-16	17.0	19.0	13.5	32.0	35.0	81.0
DIN120-10	10.5	21.0	15.5	32.0	35.0	85.0
DIN120-12	13.0	21.0	15.5	32.0	35.0	86.0
DIN120-14	15.0	21.0	15.5	32.0	35.0	88.0
DIN120-16	17.0	21.0	15.5	32.0	35.0	89.0
DIN120-20	21.0	21.0	15.5	38.0	35.0	91.0
DIN150-10	10.5	23.5	17.0	34.0	35.0	93.0
DIN150-12	13.0	23.5	17.0	34.0	35.0	94.0
DIN150-14	15.0	23.5	17.0	34.0	35.0	97.0
DIN150-16	17.0	23.5	17.0	34.0	35.0	97.0
DIN150-20	21.0	23.5	17.0	40.0	35.0	99.0
DIN185-10	10.5	25.5	19.0	37.0	40.0	97.0
DIN185-12	13.0	25.5	19.0	37.0	40.0	98.0
DIN185-14	15.0	25.5	19.0	37.0	40.0	101.0
DIN185-16	17.0	25.5	19.0	37.0	40.0	101.0
DIN185-20	21.0	25.5	19.0	40.0	40.0	103.0
DIN240-12	13.0	29.0	21.5	42.0	40.0	108.0
DIN240-14	15.0	29.0	21.5	42.0	40.0	111.0
DIN240-16	17.0	29.0	21.5	42.0	40.0	111.0
DIN240-20	21.0	29.0	21.5	45.0	40.0	113.0
DIN300-12	13.0	32.0	24.5	46.0	50.0	119.0
DIN300-14	15.0	32.0	24.5	46.0	50.0	119.0
DIN300-16	17.0	32.0	24.5	46.0	50.0	119.0
DIN300-20	21.0	32.0	24.5	46.0	50.0	122.0
DIN400-14	15.0	38.5	27.5	55.0	70.0	140.0
DIN400-16	17.0	38.5	27.5	55.0	70.0	140.0
DIN400-20	21.0	38.5	27.5	55.0	70.0	140.0
DIN500-16	17.0	42.0	31.0	60.0	70.0	150.0
DIN500-20	21.0	42.0	31.0	60.0	70.0	150.0
DIN625-16	17.0	44.0	34.5	64.0	80.0	160.0
DIN625-20	21.0	44.0	34.5	64.0	80.0	160.0
DIN800-16	17.0	52.0	40.0	75.0	100.0	195.0
DIN800-20	21.0	52.0	40.0	75.0	100.0	195.0
DIN1000-16	17.0	58.0	44.0	85.0	100.0	195.0
DIN1000-20	21.0	58.0	44.0	85.0	100.0	195.0

